

Y2000 SHADOW FORMAT & NCSN DATA CODES

blame Fred Klein for this document

revised November 8, 2006

This shadow2000.doc file is a Microsoft word document, and is also available as an Acrobat pdf file suitable for display or printing on all computers using Adobe's viewer, and as a text file shadow2000.txt. These documents can be found online in ehzftp.wr.usgs.gov/klein/docs and at the NCSN/UCB data center.

Shadow 2000 format is a kludge developed to store the most essential event and station data for local earthquakes in California. It is a good example of incremental growth. Its virtues are that it exists, several programs support it, and the NCSN catalog is presently in this format. Shadow format is rooted in old style HYPO71 phase cards, and is the same as Hypoinverse-2000 archive format. The phase format grew into the Hypoinverse-2000 archive format by filling in blanks and adding a summary line with the location and other event data as a header of each event. The next addition occurred when we needed places to store RTP and CUSP coda duration fit parameters and data to locate the CUSP archive tape and the seismograms on it. These data were put on "shadow" cards following each line of the Hypoinverse archive format. In 1999, the format was revised to store years as 4-digits, expand magnitudes to 2 decimal places, and group the parts of the 10-letter station codes together.

The structure of a full shadow format file is as follows. Like a HYPO71 phase file, a file may contain any number of events. Events within a file are in chronological order. All shadow cards begin with a \$ sign (items 2, 3, 5 and 7 below). There is one header (items 1, 2, 3) and one terminator (items 6 and 7) per event. There may be any number of stations (items 4 and 5). All formats are column oriented and there are no standard field delimiters. The FORTRAN formats below are to be used for reading the fields. Decimal points may or may not appear, and if not, their places are implied by the format as indicated.

- 1) A summary line with location and other event data;
- 2) The first summary shadow begins with "\$1" and has reference time and archive tape information for CUSP events (the fields are empty for RTP events);
- 3) Additional and optional event shadows may follow, presently to a maximum of 4, beginning with "\$2", etc.

Data for each station (of which there may be any number) follow and consist of pairs of lines:

- 1) Phase lines with data for individual stations;
- 2) Phase lines are followed by one shadow line with coda duration parameters and seismogram recovery data;

The event ends with:

- 1) A terminator card with an ID number and an optional trial hypocenter; and
- 2) The terminator shadow, presently mostly blank.

There are standard subsets of these full shadow files. Stripping out all shadow cards (lines beginning with \$) results in a basic HYPOINVERSE archive file. This form omits coda duration fit parameters and seismogram pointers. Thus pre-RTP and pre-CUSP data exist without shadow (\$) cards. Keeping only the summary header produces a catalog file of summary data suitable for programs like EQSELECT, SELECT and QPLOT.

This document also has the format of the master station location and history file calsta2000.loc. It lists every channel picked or recorded by the NCSN, their operation dates, and the various station codes including SEED used through the years.

TABLE OF CONTENTS

SUMMARY HEADER FORMAT Y2000	2
SUMMARY SHADOW FORMAT	3
MAGNITUDES	4
PREFERRED MAGNITUDE SELECTION ORDER	4
AUXILIARY EVENT REMARKS	5
STATION ARCHIVE FORMAT Y2000	5
STATION SHADOW FORMAT	7
STATION ARRIVAL TIME WEIGHTING	8
EVENT TERMINATOR FORMAT	9
EVENT TERMINATOR SHADOW	9

MASTER STATION LOCATION/HISTORY FILE (calsta2000.loc).....	9
GPS/topo datum & location status code table.....	10
FORMAT OF THE HYPOINVERSE-2000 STATION FILE.....	11
SUMMARY HYPO71 FORMAT Y2000.....	12
Table 1. DATA SOURCE CODES.....	13
Table 2. NETWORK OWNER/OPERATOR CODES.....	14
Table 3a. 3-LETTER USGS COMPONENT CODE DEFINITIONS.....	15
Table 3b. 3-LETTER SEED COMPONENT CODE DEFINITIONS.....	16
Table 3c. NCSN 3-LETTER COMPONENT (CHANNEL) CODES.....	17
Table 4. STATION OR PHASE REMARK CODES.....	20
Table 5. 1-LETTER REGION CODE.....	21
Table 6. 2-LETTER PORTABLE NET CODES.....	21
Table 7. REGIONS BY 3-LETTER CODE.....	22
Table 8. MULTIPLE VELOCITY MODELS.....	24
Table 9. WEIGHT CODES FOR TIMES, AMPLITUDES & DURATIONS.....	27

SUMMARY HEADER FORMAT Y2000

Start	Fortran		
Col.	Len.	Format	Data
1	4	I4	Year.
5	8	4I2	Month, day, hour and minute.
13	4	F4.2	Origin time seconds.
17	2	F2.0	Latitude (deg). First character must not be blank.
19	1	A1	S for south, blank otherwise.
20	4	F4.2	Latitude (min).
24	3	F3.0	Longitude (deg).
27	1	A1	E for east, blank otherwise.
28	4	F4.2	Longitude (min).
32	5	F5.2	Depth (km).
37	3	F3.2	Magnitude from maximum S amplitude from NCSN stations
40	3	I3	Number of P & S times with final weights greater than 0.1.
43	3	I3	Maximum azimuthal gap, degrees.
46	3	F3.0	Distance to nearest station (km).
49	4	F4.2	RMS travel time residual.
53	3	F3.0	Azimuth of largest principal error (deg E of N).
56	2	F2.0	Dip of largest principal error (deg).
58	4	F4.2	Size of largest principal error (km).
62	3	F3.0	Azimuth of intermediate principal error.
65	2	F2.0	Dip of intermediate principal error.
67	4	F4.2	Size of intermediate principal error (km).
71	3	F3.2	Coda duration magnitude from NCSN stations.
74	3	A3	Event location remark. (See table 7 below).
77	4	F4.2	Size of smallest principal error (km).
81	2	2A1	Auxiliary remarks (See note below).
83	3	I3	Number of S times with weights greater than 0.1.
86	4	F4.2	Horizontal error (km).
90	4	F4.2	Vertical error (km).
94	3	I3	Number of P first motions.
97	4	F4.1	Number of NCSN S-amplitude mags with weights>0.
101	4	F4.1	Number of NCSN duration mags with weights>0.
105	3	F3.2	Median-absolute-difference of NCSN S-amp magnitudes.
108	3	F3.2	Median-absolute-difference of NCSN duration magnitudes.
111	3	A3	3-letter code of crust and delay model. (See table 8 below).
114	1	A1	Last authority for earthquake N=NCSC (USGS), B=UC Berkeley. (A T in this column is meaningless)
115	1	A1	Most common P & S data source code. (See table 1 below).
116	1	A1	Most common duration data source code. (See cols. 71-73)
117	1	A1	Most common amplitude data source code.
118	1	A1	Coda duration magnitude type code

119	3	I3	Number of valid P & S readings (assigned weight > 0).
122	1	A1	S-amplitude magnitude type code
123	1	A1	"External" magnitude label or type code. Typically L for ML or W for MW. This information is not computed by Hypoinverse, but passed along, as computed by UCB.
124	3	F3.2	"External" magnitude.
127	3	F3.1	Number of "external" magnitudes with weights>0.
130	1	A1	Alternate amplitude magnitude label or type code (i.e. L for ML calculated by Hypoinverse from Wood Anderson amplitudes).
131	3	F3.2	Alternate amplitude magnitude.
134	3	F3.1	Number of alternate amplitude mags with weights>0.
137	10	I10	Event identification number
147	1	A1	Preferred magnitude label code chosen from those available.
148	3	F3.2	Preferred magnitude, chosen by the Hypoinverse PRE command.
151	4	F4.1	Number of preferred mags with weights>0.
155	1	A1	Alternate coda duration mag label or type code (i.e. Z).
156	3	F3.2	Alternate coda duration magnitude.
159	4	F4.1	Number of alternate coda duration mags with weights>0.
163	1	A1	QDDS version number of information. Starts at 0 for quick look reports. Incremented by one each time new information is added or revised: from quick location, final earthworm location with MD, ML added, etc.
164	1	A1	"Origin instance" version number, distinguishes between different origins (hypocenters). It starts with 'a' ('0' for quick-look reports) and runs through the alphabet. When Berkeley has a final magnitude for each origin, the character is promoted to upper-case.
165	2	A2	Code for domain (ie. NC, CI) in which the location was made.
167	2	A2	Code for processing version (ie 01, 02) of set of location files.

SUMMARY SHADOW FORMAT

Most of these fields hold CUSP related data. If the event was only on the RTP or earthworm and CUSP did not digitize the event, all fields up to col. 80, except the "\$1" identifier are blank. This format did not change with the Y2000 revision. Any data beyond column 80 is erroneous.

Cols	Len.	Format	Data
1-2	2	'\$1'	Designates Shadow Summary Card
3-6	4	I4	Reference time: year
7-10	4	2I2	Reference time: month, day
11-14	4	2I2	Reference time: hour, minute
15-20	6	F6.3	Reference time: seconds
First Arkive Tape:			
21-23	3	A3	Network Identifier (e.g. CAL, CIT, HVO)
24	1	1X	blank
25-34	10	I10	Arkive tape number
35-44	10	I10	Arkive event id number
45-50	6	I6	File number on Arkive tape
Second Arkive Tape (rare):			
51-53	3	A3	Network Identifier
54	1	1X	blank
55-64	10	I10	Arkive tape number
65-74	10	I10	Arkive event id number
75-80	6	I6	File number on Arkive tape

MAGNITUDES

The NCSN computes several types of magnitudes, depending on the type of data available, the era of network operation, and the size of the earthquake. The "primary" magnitudes are those that are available for most events, particularly events less than magnitude 3.5. Because the primary magnitudes saturate for events above M4.5, the NCSN also computes "alternate" magnitudes (coda or amplitude) from low-gain instruments that generally remain on-scale during large earthquakes. We also provide "external" local magnitudes (ML) computed by UC Berkeley. Where available, the UC Berkeley magnitude supercedes the USGS magnitude.

Because each magnitude is appropriate for a given magnitude range, we provide a "preferred" magnitude in columns 148-150. The logic for selecting the preferred magnitude is shown in the table below. It attempts to provide the most reliable estimate for each earthquake. Going down the table, as soon as a magnitude satisfies the criteria, it is chosen as preferred. Note that variations in magnitude estimates are expected when using different methods. There is no "correct" magnitude. The preferred magnitude may have unusual statistical properties because it is drawn from different magnitude types.

Magnitude fields are filled only if the magnitudes were calculated. A "zero" magnitude value means none was calculated. Each magnitude is in a fixed position. Alternate magnitudes use the label codes given by the Hypoinverse FC2 and XC2 commands, or the external label code.

CODE EXPLANATION

PRIMARY MAGNITUDES

D Coda duration magnitude (Eaton, BSSA, v.82 p.533, 1992).
Uses all components. Formerly code E.
X S-wave maximum amplitude magnitude. Eaton, BSSA, v.82 p.533, 1992).
Uses all components.

EXTERNAL MAGNITUDES

L Local magnitude as computed by UC Berkeley
S Surface wave Ms
W Moment magnitude
G Geysers net duration mag computed by LBL (uncalibrated)

ALTERNATE MAGNITUDES

L Local magnitude computed by NCSN from UCB Wood Anderson amplitudes.
Z Low gain (Z comp) coda duration magnitude of Hirshorn and Lindh (1989?).
P Initial P-wave amplitude magnitude. Uses all components. Not in use.
G Low-gain initial P-wave amplitude magnitude. Uses low-gain Z component.
Not in use.
A S-wave maximum amplitude magnitude for which amplitude data are lost.

PREFERRED MAGNITUDE SELECTION ORDER

Order	label code	label column	mag columns	sum_mag_wts columns	mag_MAD columns	min # readings	min mag	type
1.	L or W	123	124-126	127-129	N/A	0	3.0	"external"
2.	D	118	71- 73	101-104	108-110	1	0.0	"primary dur"
3.	X or A	122	37- 39	97-100	105-107	1	0.0	"primary amp"
4.	L	130	131-133	134-136	N/A	4	4.0	"alternate amp"
5.	L or G	123	124-126	127-129	N/A	0	0.0	"external"
6.	L	130	131-133	134-136	N/A	0	0.0	"alternate amp"

AUXILIARY EVENT REMARKS

Assigned by analyst (col. 81):

Q Quarry blast
R Explosion, as for a refraction source (formerly code E)
N NTS blast
F Felt
M Multiple event (Two events close in time and space are each marked M)
B Blast (HVO)
T Tremor associated (HVO)
L Long period (HVO)

Assigned by HYPOINVERSE (col. 82):

Location had convergence problems such as maximum number of iterations or failure to reach a minimum RMS.
- Depth was poorly constrained and was held fixed at its current value.
X Location fixed to trial hypocenter.

STATION ARCHIVE FORMAT Y2000

The following line appears for each station. If CUSP digitized the event, an entry may appear for saved traces such as time code or stations from which no information was measured. The unique designation of a station name has expanded with time, reflecting the increase in sensor types and conflicts with station names in use by other networks. We formally define a station name with 10 letters as the concatenation of the 5-letter site code, 2-letter network code, and 3-letter component code. An additional 2-letter location code will be used in the future to accommodate cases where the other fields would be the same. Hypoinverse optionally uses 1 or 3 letter component codes, and both are listed in the print file. NCSN practice is to use the 3-letter code for station matching, and the 1-letter code as a convenience label only. The number of decimal places N is implied by the fortran format (ie F5.N).

Station archive format Y2000

Start	Fortran	
Col.	Len.	Format Data
1	5	A5 5-letter station site code, left justified.
6	2	A2 2-letter seismic network code.
8	1	1X Blank
9	1	A1 One letter station component code.
10	3	A3 3-letter station component code.
13	1	1X Blank
14	2	A2 P remark such as "IP".
16	1	A1 P first motion.
17	1	I1 Assigned P weight code.
18	4	I4 Year.
22	8	4I2 Month, day, hour and minute.
30	5	F5.2 Second of P arrival.
35	4	F4.2 P travel time residual.
39	3	F3.2 Normalized P weight actually used.
42	5	F5.2 Second of S arrival.
47	2	A2 S remark such as "ES".
49	1	1X Blank
50	1	I1 Assigned S weight code.
51	4	F4.2 S travel time residual.
55	7	F7.2 Amplitude (Peak-to-peak in Develocorder or paper mm).
62	2	I2 Amp units code. 0=PP mm, 1=0 to peak mm, 2=dig. counts.
64	3	F3.2 S weight actually used.
67	4	F4.2 P delay time.
71	4	F4.2 S delay time.
75	4	F4.1 Epicentral distance (km).
79	3	F3.0 Emergence angle at source.
82	1	I1 Amplitude magnitude weight code.
83	1	I1 Duration magnitude weight code.
84	3	F3.2 Period at which the amplitude was measured for this station.
87	1	A1 1-letter station remark. (See table 4 below).
88	4	F4.0 Coda duration in seconds.
92	3	F3.0 Azimuth to station in degrees E of N.
95	3	F3.2 Duration magnitude for this station.
98	3	F3.2 Amplitude magnitude for this station.
101	4	F4.3 Importance of P arrival.
105	4	F4.3 Importance of S arrival.
109	1	A1 Data source code (See table 1 below).
110	1	A1 Label code for duration magnitude from FC1 or FC2 command.
111	1	A1 Label code for amplitude magnitude from XC1 or XC2 command.
112	2	A2 2-letter station location code (unused at present).
114	2	I2 Amplitude type 0=unspecified 1=Wood-Anderson 2=velocity 3=acceleration 4=no magnitude
116	3	A3 Alternate 3-letter component code (USGS or SEED)
119	1	A1 X if station amplitude magnitude was not used in event mag.
120	1	A1 X if station duration magnitude was not used in event mag.

STATION SHADOW FORMAT

The shadow format differs for RTP and CUSP data. Columns 1-41 are the same for both. You can discriminate between RTP and CUSP shadows before reading them by looking on the phase card. RTP phases will have a data source (col. 109) of R, P, or M and (usually) corresponding P remark (cols. 14-15) of XP, YP and ZP. Earthworm data follows the RTP format, but has a data source code of W. Any data beyond column 92 is erroneous.

The coda duration fit parameters result from a fit of the coda envelope to the form $10^{**}A * t^{**}-Q$ where $10^{**}A$ is in units of digital counts and t is in seconds after the P time. If Q is fixed at 1.8 (QFIX), the resulting A is AFIX below. If both are fit simultaneously, AFREE and QFREE are stated below. For more on coda duration fitting see Carl Johnson's thesis (Caltech 1979) or Hirshorn et al., Real Time Signal Duration Magnitudes from Low-gain Short Period seismometers, USGS Open File Report 87-630, 1987.

For RTP data, the AMH tuple provides data for cols 44-50. Up to six time/amplitude data pairs describing the coda duration decay are written. See Al Lindh for a description of these data.

RTP, EARTHWORM AND CUSP

Cols.	Format	Data
1-2	'\$ '	Designator for shadow phase card.
3-5	I3	No. of (averaged) amplitude windows used in coda duration fit algorithm.
6-10	F5.2	AFIX (see above).
11-15	F5.2	QFIX (see above).
16-20	F5.2	AFREE (see above).
21-25	F5.2	QFREE (see above).
26-30	F5.2, 1X	RMS of L1 fit to coda duration amplitude windows.
32-35	A4	Coda phase descriptor (See table below).
36-40	I5, 1X	Coda duration time (seconds) as measured directly i.e., not recalculated.

CUSP ONLY

Cols.	Format	Data
42-45	'AHS '	Amplitude descriptor, peak S-wave half amplitude value as computed for MCD tuple.
46-50	I5	Amplitude corresponding to phase card cols 42-45
51	'1'	First/Second arkive tape source
52-53	I2	CUSP set number for these phase data
54-57	I4	CUSP pin number for these phase data
58-67	I10	Offset: number of words in Arkive file before first word of the seismogram
68-77	F10.5	Toffset: offset time of first data point for this seismogram, relative to reference time in cols 4-19 of shadow summary card.
78-84	I7	Nwords: number of words in this seismogram
85-92	F8.6	Digint: digitization interval, seconds
93-95	A3	Digitizer device code (see table 1)

RTP AND EARTHWORM

42-43	'PH'	Amplitude descriptor, peak P-wave half amplitude
44-45	A1, I1	Phase descriptor and weight assigned by RTP to the amplitude it reports; e.g. P0. Weight code is the number of the first 3 P peaks that clipped. From indices(2,3) of the PHASE attribute of the AMH tuple.
46-50	I5	Amplitude corresponding to cols 42-45, from the AMP attribute of AMH tuple. PERiod attribute is available but is not written out.

51-57	I3,I4	Time-amplitude data pair #1
58-64	I3,I4	Time-amplitude data pair #2
65-71	I3,I4	Time-amplitude data pair #3
72-78	I3,I4	Time-amplitude data pair #4
79-85	I3,I4	Time-amplitude data pair #5
86-92	I3,I4	Time-amplitude data pair #6
93-95	A3	Digitizer device code (see table 1)

4-LETTER CODA DESCRIPTOR

First letter:

P Normal termination of coda; RTP codas < 144 sec.
 S Short or premature termination of coda; recalculated RTP codas > 144 sec.
 N Noisy coda with early termination. RTP gave a negative duration time.
 K Signal clipped to end of time series.

Second letter:

T Bad coda duration computed using the wrong clipping value (CUSP only).
 S Normal case of coda duration longer than S-P time.
 P P coda; duration less than S-P time.

Third letter:

_ (space) Did not do a coda fit.
 X Coda duration is from a fixed L1 norm fit to the average absolute amplitudes.
 R Coda duration is from a free L1 norm fit to the average absolute amplitudes.
 N Normal coda, no fits were necessary.

Fourth letter

0-4 Coda weight (0=full weight, 4=no weight).

STATION ARRIVAL TIME WEIGHTING

This is a brief description of the types of weight factors applied to P and S times in the hypocenter inversion. The final weight actually used (output in columns 39-41 of the station archive record) is the product of 3 factors: 1) the assigned weight, 2) the distance weight, and 3) the residual weight. After all weight terms are multiplied together, the resulting station weights are normalized so the weights total the integer number of station times used in the inversion.

The assigned weight is input as a 1-digit code in col 17. The assignment is made by the analyst or picker software and depends on the impulsiveness or emergence of the waveform. 0 is full weight (1.0), 1 is 0.5, 2 is 0.2, 3 is 0.1 and codes 4-9 are no (0.0) weight. Usually codes 5-9 are reserved for "outweighted" readings that have had a 5 added to their initial weight codes because it is a duplicate reading or because the reading does not fit the solution at all. See table 9.

The distance weight out-weights distant stations whose travel times are poorly modeled. When the distance to the second closest station (D2) is less than 15 km, stations closer than 52.5 km are given full weight, stations farther than 105 km are given no weight, and a cosine taper is used between. When D2 is more than 15 km, stations closer than D2*3.5 km are given full weight, stations farther than D2*7.0 km are given no weight, and a cosine taper is used between. This expands the distance weighting when the earthquake is outside or in a thin part of the network. Distance weighting is applied only after the 4th iteration when the solution has stabilized.

The residual weight out-weights stations whose residuals are large because they are often mis-picked. When the RMS residual is less than 0.10 sec, stations with residual less than 0.20 sec are given full weight, stations with residual more than 0.30 sec are given no weight, and a cosine taper is used between. When the RMS residual is more than 0.10 sec, stations with residual less than 2*RMS sec are given full weight, stations with residual more than 3*RMS sec are given no weight, and a cosine taper is used between. This expands the weighting to include more stations for poor, high RMS events. Residual weighting is applied only after the 4th iteration when the solution has stabilized.

EVENT TERMINATOR FORMAT

Normally the event terminator will contain only the event ID number. It signals the end of an event because the station code is blank. Fields are reserved for an optional trial hypocenter or fixed depth control. HYPOINVERSE may use either this trial hypocenter or the hypocenter on the event header. See the HYPOINVERSE documentation for more information on trial hypocenters.

<u>Cols.</u>	<u>Format</u>	<u>Data</u>
1-4	4X,2X	Must be blank.
7-10	2I2	Trial hour and minute.
11-14	F4.2	Trial second.
15-16	F2.0,1X	Trial latitude (deg).
18-21	F4.2	Trial latitude (min).
22-24	F3.0,1X	Trial longitude (deg).
26-29	F4.2	Trial longitude (deg).
30-34	F5.2	Trial depth (a negative value fixes depth).
35-62	28X	blank
63-72	I10	ID number

EVENT TERMINATOR SHADOW

1-2	'\$ '	Shadow card designator
3-62	60X	blank
63-72	I10	ID number

The following tables were modified from Klein et al., Seismic Station Data for Northern California and Surrounding Areas, USGS Open File Report 88-448, 1988.

MASTER STATION LOCATION/HISTORY FILE (*calsta2000.loc*)

Although not part of the shadow format or catalog phase data, this file is often read by users of the catalog.

The file *calsta2000.loc* presently resides in Menlo Park on andreas.wr.usgs.gov in `/home1/calnet/klein/stas/` and also in `ftp anonymous in ehzftp.wr.usgs.gov/klein/stations`. Additional stations not currently used in NCSN phase data are in *more2000.loc* in the same directories.

The file *calsta2000.loc* has the complete history of the NCSN network. The file has most stations in the surrounding networks but is not updated as frequently. The on and off dates are as accurate as possible. *Calsta2000.loc* also has the station name history. Codes are here for pre-1977 (4-letters), 1977-1986 (4-letters including component), 1986-1994 (5-letters including net and component), and 1994-2006 (10-letters including net and component). The "unique" or "universal" station codes consist of a 3-5 letter site code, 2-letter net code and 3-letter USGS component codes. The 1-letter component code is used as a label in various station files, but is not unique. Starting in 2006, it is expected that 3-letter SEED component codes will be used instead of the USGS codes. The ambiguity of SEED codes, together with station moves, also requires 2-letter location codes. The SEED station codes consist of a 3-5 letter site code, 2-letter net code, 3-letter SEED component codes, and a 2-letter location code. The location code "—" is used as a default for station where a location code tie-breaker is not required.

Most NCSN stations with coordinates to 4 decimal places of minutes of lat/lon have been surveyed with GPS instrumentation. These precise locations have mostly replaced the locations estimated from a topographic map, that are all that is available for abandoned sites. The elevation at these GPS sites is referenced to the geoid instead of sea level.

<u>cols.</u>	<u>length</u>	<u>heading</u>	<u>data</u>
1-5	5	SITE	Station site code (within its own network)
6-7	2	NET	Unique station net code (assigned by IRIS)
9-11	3	USGS	USGS component (channel) code (SEED for some digitals)
These 3 fields are the "unique" station code (1994-2006).			
13-15	3	RATN	Station name code (Rationalized code 1986-94)
16	1		1-letter network code (Rationalized code 1986-94)
18	1	C	1-letter component code (Rationalized code 1986-94)

21-24	4	4LET	"New" 4-letter code 1977-86, 4 th letter is the component
26-29	4	OLD	"Old" or standard code (pre-1977 for USGS)
31-32	2	LAT	North latitude, degrees
34-40	7		North latitude, minutes (F7.4)
42-44	3	LON	West longitude, degrees
46-52	7		West longitude, minutes (F7.4)
55-58	4	ELEV	Elevation, meters
60	1	R	Geographic region code of Eaton
61	1	G	GPS/topo datum & location status code (see below)
63-84	22		Full geographic name. "&" in col 84 if the channel is a duplicate and temporary alias name no longer used (DDI aka HV1) or an additional decimation with the same SNC code.
85	1		Colon (:) if non-USGS station recorded in Menlo Park, Semi-colon (;) if non-USGS station formerly recorded in MP Comma (,) if non-USGS station maintained but not recorded, or used in another station database.
86-89	4	ORG	Network owner/operator code
90-97	8	OPERATN	Start date of operation of instrument (YYYYMMDD)
99-106	8		End date of operation of instrument (YYYYMMDD)
109-116	8	DATAUSE	Start date of USGS-MP usage of data (YYYYMMDD)
118-125	8		End date of USGS-MP usage of data (YYYYMMDD)
127-129	3	SEED	SEED code for component, non-unique mapping to USGS code.
131-132	2	LOC	2-letter location code for breaking ties, not used yet.
134-137	4	ON	On time (hr-min GMT) of start date of operation.
139-142	4	OFF	Off time (hr-min GMT) of end date of operation.
144-147	4	JPE	Jerry Eaton's station name. Same as 4-letter name for USGS-Menlo stations.
149-152	4	ALIAS	Alias, erroneous or unofficial name.
154-157	4		Additional alias, erroneous or unofficial name.

GPS/topo datum & location status code table

(see spreadsheet.txt for more notes about the use of this location status code in the NCSN)

code definition:	comment:
A WGS84 handheld GPS of sensor	Most common NCSN case, within 2 meters of sensor
B WGS84 sensor offset from GPS	Offset (distance & azimuth) estimated from nearby GPS location
E WGS84 GPS external antenna	Self-reported GPS of telemetry antenna
N WGS84 nearby handheld GPS	GPS of nearby, outdoor location
D WGS84 hi-acc differential GPS	The highest accuracy GPS we can do (seldom used)
C WGS84 from topo map location	Never GPS'ed, converted from topo map
T NAD27 topo map	Never GPS'ed, from topo map only, ie from abandoned site
W WGS84 either antenna/sensor	GPS exact site undocumented
blank Not yet determined.	

FORMAT OF THE HYPOINVERSE-2000 STATION FILE

This is the format of the station file read by the Hypoinverse2000 location program. Although not part of the shadow format or catalog phase data, this file is often read by users of the catalog. NCSN uses a computer program called STADCK to read calsta2000.loc and write a Hypoinverse2000 station file for a specified time period. This format list is from the Hypoinverse2000 manual. Most of the delay, calibration or magnitude correction fields will be undefined in most versions of this file, and the values will be defined later in the catalog processing.

Start		Fortran	
Col.	Len.	Format	Data
1	5	A5,1X	Station site code. The first character may not be the \$ character.
7	2	A2,1X	Seismic network code.
10	1	A1	Optional 1-letter station component code.
11	3	A3,1X	3-letter component or channel code.
15	1	A1	Station weight code (in units of 0.1) by which the weights assigned each P & S phase are to be multiplied. Use the digits 0-9 for the weight in tenths; "*" or "0" for no weight; or any other character (including blank) for full weight.
16	2	I2, 1X	Latitude, degrees.
19	7	F7.4	Latitude, minutes.
26	1	A1	N or blank for north latitude, S for south.
27	3	I3, 1X	Longitude, degrees.
31	7	F7.4	Longitude, minutes.
38	1	A1	W or blank for west longitude, E for east.
39	4	4X	Reserved for elevation in m. Not used by HYPOINVERSE.
43	3	F3.1,2X	Default period (in sec) at which the maximum amplitude will be read for this station. Must be greater than 0.1.
48	1	A1	Put a "2" or "A" here to designate this as an alternate crust model station. Both alternate and primary crustal models must be in use. Stations may also be tagged for use with an alternate model in the delay file.
49	1	A1	Optional station remark field to copy to print output.
50	5	F5.2, 1X	P delay (sec) for delay set 1.
56	5	F5.2, 1X	P delay (sec) for delay set 2.
62	5	F5.2	Amplitude magnitude correction. If in the range +/-2.4, the correction is included (by addition) in the amplitude magnitude. If you don't want a station's magnitude used in the event magnitude, use a correction of 5.0 plus the actual correction. You can also assign a zero weight (see next).
67	1	A1	Amplitude magnitude weight code. Codes 0-9, "*" and blank are used the same as the P & S weight codes (col 15). The actual magnitude weight used is the product of those on the station and phase cards. See also col 62.
68	5	F5.2	Duration magnitude correction (works the same as the amplitude magnitude correction).
73	1	A1	Duration magnitude weight code (works the same as the amplitude weight code).
74	1	I1	Instrument type code.
75	6	F6.2	Calibration factor.
81-82	2	A2	2-letter location code (component extension)

SUMMARY HYPO71 FORMAT Y2000

The real-time computers in Menlo Park, among others, produce data in this format. It is more readable than, but is a subset of the Hypoinverse format. For code definitions, such as data source code, see other tables in shadow.doc. The format is identical to the pre-Y2000 format except that the years are expanded to 4-digits, everything is moved 2 cols to the right, and the 3-letter location is added on the end.

* indicates a new/revised field

<u>Start</u>		<u>Fortran</u>	
<u>Col.</u>	<u>Len.</u>	<u>Format</u>	<u>Data</u>
1	4	I4	Year *
5	4	2I2	Month and day.
9	1	1X	Must be blank
10	4	2I2	Hour and minute.
14	6	F6.2	Origin time seconds.
20	3	F3.0	Latitude (deg).
23	1	A1	S for south latitude, blank otherwise.
24	5	F5.2	Latitude (min).
29	4	F4.0	Longitude (deg).
33	1	A1	E for east longitude, blank otherwise.
34	5	F5.2	Longitude (min).
39	7	F7.2	Depth (km).
46	1	1X	Blank
47	1	A1	Magnitude type code.
48	5	F5.2	Magnitude.
53	3	I3	Number of P & S times with weights greater than 0.1.
56	4	F4.0	Maximum azimuthal gap.
60	5	F5.1	Distance to nearest station (km).
65	5	F5.2	RMS travel time residual.
70	5	F5.1	Horizontal error (km).
75	5	F5.1	Vertical error (km).
80	1	A1	Remark: Q if Quarry blast.
81	1	A1	Remark: Quality flag A-D.
82	1	A1	Remark: Data source code. (See table 1; ie W= earthworm).
83	1	1X	Blank
84	10	I10	Event identification number
94	1	1X	Blank
95	1	A1	QDDS version number of information. Starts at 0 for quick look reports. Incremented by one each time new information is added or revised: from quick location, final earthworm location with MD, ML added, etc.
96	1	A1	"Origin instance" version number, distinguishes between different origins (hypocenters). It starts with 'a' ('0' for quick-look reports) and runs through the alphabet. When Berkeley has a final magnitude for each origin, the character is promoted to upper-case.

Table 1. DATA SOURCE CODES

(_ stands for a blank space. The code in [], or the last 3 letters of the 6-letter code is the CUSP digitizer device code)

1-let-code	Meaning	Original 6-letter codes
<u>Analog stations only (readings, no seismograms)</u>		
H	Hand timed	H_____ 1_____ CALNEW CALDVL CALHEL
R	Main RTP	XP P-remark. May find: R_____ 2_____ CALRTP
P	Prototype RTP	YP P-remark. May find: CALPRO
O	Motorola RTP	CALMOT
W	Earthworm (real time picks, no seismograms)	
J	Jerry Eaton hand timed	
U	U. Nevada Reno readings	RENO__ _ENO__ RENO_1
B	UC Berkeley readings	
Y	Woodward-Clyde readings	
T	Tera Corp. or PG&E readings	

<u>Analog stations digitized at a central site (seismograms available)</u>		
2	CUSP Tustin A/D #2	CALT2_ _ALT2_ [T2]
4	Pasadena Tustin #2	CITT2_
8	Pasadena VAX digitized	CITFMT
E	CUSP-Eclipse digitized from FM tape	CALECL _ALECL [ECL]
F	CUSP-VAX/750 digitized from FM tape	CALFMT CALFM3 CALFT3 [FM]
N	CUSP/Earthworm National digitizer	[NTL]
C	HVO CUSP (supported, but unused in NCSN catalog)	[OBI], [XOB]
0	(zero) CUSP/Tustin at Reno, 1980's to 1/1/2000	
9	presently unused	

<u>Analog stations digitized at a non-Menlo digitizer generally using earthworm</u>		
I	Imported National digitizer grams from Reno	[IM1]
Z	Imported National digitizer grams from Simmler (Caltech)	[IM2]
V	Imported National digitizer grams from Bakersfield (Caltech)	[IM3]
S	Imported National digitizer grams from Pasadena (Caltech)	[IM4]
G	Imported National digitizer grams from Edwards AFB (Caltech)	[IM5]
g	Imported National digitizer grams from Diablo Can. (PG&E)	[IM6]
M	Imported National digitizer grams from Ft. Scotty (Caltech)	
Q	National digitizer at Mammoth	[ML1]
C	National digitizer at Geyser Peak	[GP1]
K	National digitizer at Carr Hill	[CH1]
L	National digitizer at Sonoma Mountain	[SM1]
1	National digitizer at Mount Tamalpais	[TM1]
3	National digitizer at Vollmer Peak	[VP1]
5	National digitizer at Lawrence Livermore N.L.	[LL1]
6	National digitizer at Fremont Peak	[FP1]
7	National digitizer at Hollister	[HO1]_
X	Analog 50 sps digitized by Nanometrics HRD	[HRX] Trident [BM1], [WH1]
D	Calif. Department of Water Resources ("soon" after 9/03)	[DWR]

"Digital" stations

A	Digitized at seismometer (e.g. Nanometrics [HRD], digital seismic telemetry units [DST], Reftek [REF, RNW], Kinematics [K2], Reno Reftek [R32], [RF1], Quanterra [QS1])
?	(or blank) Unknown or undefined

Table 2. NETWORK OWNER/OPERATOR CODES

The N code was the 1-letter net code formerly used by Menlo Park. In the former usage, it was the fourth letter of the 4-letter station code, for example "CALM".

The IRIS code is now the official net code used with station site codes. In addition to regular NCSN stations, NC is also used for defunct nets for which the USGS archives phase data. A unique net code allows nets to duplicate each other's site codes. The NEIS code was used in publications such as the Historical Survey of US Seismic Stations (Poppe, USGS Prof Paper 1096) and Seismograph Station Codes & Coordinates (Presgrave et al, USGS Open File Report 85-714). The ORG code is used in Menlo's master station history file calsta2000.loc.

	IRIS	NEIS	ORG	Operator
N code	code	code	code	
A				Special purpose, i.e a tie-breaker
B	BK	BRK	UCB	UC Berkeley, including digital seismic network BDSN
C	CI	PAS	GSP	Caltech-USGS Pasadena
C	CI		GSPM	Formerly operated by Menlo, now by Pasadena
C	CI	PAS	CIT	Caltech, original pre-USGS stations
C*	TS*		CIT	Caltech terrascope (BAR,GSC,ISA,MLA,PAS,PFO,SBC,SVD)
D	SN		GSD	Southern Nevada Net (UN Reno, formerly USGS Denver)
F	PX		UCS	Parkfield net (Duke/UC Santa Barbara/Berkeley/USGS)
G	NC	CDMG	CDM	Calif. Div. of Mines and Geology
L	NC	LAC	LLL	Lawrence Livermore Labs, Livermore net
L	LL	LAC	LLL	Lawrence Livermore Labs, NTS net
M	NC	MNLO	GSM	USGS Menlo
M	NC	MNLO	GSMP	Formerly operated by Pasadena, now by Menlo
O	UW		UWA	Univ. of Washington Oregon stations
P	NC		5DY,DIG,SMO,CEN	USGS Menlo portables
P	NC			(Non-USGS portables use P and UNR, CIT etc.)
R	NN	REN	UNR	Northern Nevada (Univ. of Nevada Reno)
S	LA	USC	USC	Univ. of Southern Calif., now merged with CI.
T	NC		TER	Terra Corp. (Mendocino area)
U	UU		UUT	University of Utah regional network
W	WR	CDWR	DWR	Calif. Div. of Water Resources
X	MX	ECX	ECX	Mexican national network, CICESE, Ensenada, Mexico
Y	NC		WCC	Woodward-Clyde & PG&E (Sierra foothills)
Y	PG		PGE	Pacific Gas & Electric Co. (Diablo Canyon)
	AZ		UCSD	Anza network, UC San Diego
	CE		CDMG	Calif. Div. of Mines and Geology strong motion
	GO		NEIC	USGS National Earthquake Info Center -Golden Network
	NP		NSMP	National strong motion program (accelerographs)
	SD?		SD	UC San Diego, So. Calif. Earthquake Center
	US		NEIC	US National network, ANSS backbone of USGS/NEIC
	XL		GSM	USGS Menlo portable deployments starting in 1998, which may not follow any standard portable naming.
	XN		DUK	Duke Univ. portable deployment, Mammoth area 1997.

* Caltech's broadband Terrascope stations now use the net code CI because of intermixing with the short period network.

Table 3a. 3-LETTER USGS COMPONENT CODE DEFINITIONS

This table defines the letters used in the NCSN channel definitions. The NCSN channel identifier distinguishes different components at the same station site. For older analog stations, NCSN codes differ from SEED codes (table 3b), but for newer digital stations, NCSN uses SEED-compatible codes. The NCSN naming condenses all component information into 3 letters. CUSP and NCSN software do not have space for separate gain and transmission path codes and condenses this information into the NCSN 3-letter code. In the case of broadband stations and most UCB stations, NCSN uses the SEED codes. Newer channel parlance can use a 2-letter “location” code to enhance the SEED code by distinguishing between similar channels that would have the same SEED code, but the location code has not yet (as of 9/00) been implemented by the NCSN.

The first NCSN letter describes the sensor type and frequency band, the second the gain and the third the sensor orientation or direction. All network channels must use these standard codes to allow ready identification of channels. For example, the standard short-period vertical network station uses the code VHZ. The equivalent NCSN 1-letter code is V. In some contexts, the 3-letter codes can be abbreviated to the older 1-letter codes.

An astute observer will observe that neither NCSN nor SEED codes are applied consistently with the definitions. The net codes should keep the 10-letter codes for each channel unique, however.

Sensor type and frequency band (first letter of 3-letter code)

V short period seismometer (i.e. L4C)
E short period seismometer (some digital stations, SEED convention)
A accelerometer or FBA
B broadband or Streckheisen (i.e. STS-2)
W Wood-Anderson
L long period seismometer (used for digitally transmitted terrascope data)
D dilatometer
T time trace
H short period seismometer (often downhole)
X Experimental

Gain (including telemetry type and dynamic range) (second letter)

H high gain (12-24 db attenuation for USGS seismometers)
M medium gain [proposed, presently unused]
L low gain seismometer (42-48 db attenuation for USGS seismometers)
N accelerometer
F very low gain (72 db attenuation for USGS seismometers)
S strong motion (very very low gain)
D high gain, digital telemetry, high dynamic range

Orientation (third letter; these are the same as the SEED codes)

Z vertical
E east-west
N north-south
1,2,3 non-traditional or unknown orientations
I or blank no orientation, isotropic component
(dilatometer, hydrophone, time trace)

Table 3b. 3-LETTER SEED COMPONENT CODE DEFINITIONS

SEED (Standard for the Exchange of Earthquake Data) channel code definition is found in appendix A of the SEED manual. The relevant parts of the definition are restated here. The first column of the SEED code is the band code (sample rate and corner period), the second is the instrument type (including gain) and the third is the orientation.

Band code

	Band type	sample rate	corner period
E	extremely short period	≥ 80 hz	< 10 s
S	short period	≥ 10 to < 80	< 10
D	very very short period	~ 500 hz	
H	high broad band	≥ 80	≥ 10
B	broad band	≥ 10 to < 80	≥ 10
M	mid period	> 1 to < 10	
L	long period	~ 1	
V	very long period	~ 0.1	
U	ultra long period	~ 0.01	
R	extremely long period	~ 0.001	
A	administrative		
W	weather		
X	experimental		

Instrument code

H	high gain seismometer	
L	low gain seismometer (formerly also used for SEED accelerometers)	
N	accelerometer	
G	gravimeter	
M	mass position seismometer	
Z	synthesized beams	
A	tiltmeter	
P	very short period seismometer (5-10 or higher hz)	
F	magnetometer	
B	creepmeter	
S	linear strainmeter	
V	volumetric strain	
T	tide meter	
R	rainfall	
O	water current	
W	wind	
K	temperature	
I	humidity	
D	pressure	
U	bolometer	
E	electronic test point	
Q	electric potential	
C	calibration input	X (experimental?), J, Y unused

Orientation code

ZNE	vertical, NS, EW
ABC	triaxial (along the edges of a cube turned up on a corner)
TR	transverse, radial
123	orthogonal, nontraditional or borehole
UWV	optional

Table 3c. NCSN 3-LETTER COMPONENT (CHANNEL) CODES

The 3-letter USGS codes (which are sometimes abbreviated to a non-unique 1-letter) are used by NCSN. This table should list all possible 3-letter USGS component codes found in the catalog in the column marked USGS. The SEED code is the equivalent standard code for data exchange (table 3b), and is in use with some USGS stations. In general, USGS=SEED codes are used for “digital” stations and USGS codes are for analog stations. Some channel types for some stations are present in this table and the catalog with two different codes. This is equivalent to the case of backward non-uniqueness from the SEED code to the USGS code (see footnote 1). Examples of double representation (backward non-uniqueness) include: (1) the USGS code (like VDZ) and the newer SEED code (EHZ) can both be in the catalog, even for the same station at different times; (2) older UCB stations in the merged USGS-UCB catalog are present twice (eg. WLN for the USGS version, and EHN for UCB Wood-Anderson: data can be present for one code, the other, or both.); (3) some identical high gain vertical stations use the SHZ code when from the UCB catalog and VHZ when from the USGS catalog. SHZ normally refers to 50 sample per sec data, and may be a 20 sps decimated version of a 100 sps VHZ station.

This messy USGS code situation was addressed in 2004. A large table of channels recorded by the USGS-Menlo Park now has both the USGS code, the SEED code, and the 2-letter “location” code that is sometimes used to supplement and break ties when two USGS codes translate to the same SEED code. The location code may appear below as a supplement to the SEED code. This “spreadsheet” table also has time-dependent gain, response, sample rate, field visit, decimation, sensor moves, serial numbers, digitizers, sensor and digitizer sensitivity information for every channel for every epoch. Tables also rename specific channels to avoid errors and duplicating codes. As of Oct 2004, seismograms have been renamed to SEED compatible channel and location codes, but the catalog of picks and locations has not.

1 USGS SEED

USGS velocity seismometer stations:

V	VHZ	EHZ ¹	vertical high gain velocity (0-30 db attenuation, gen. 12 or 18)
Z	VLZ	ELZ	vertical low gain " (36-48 db attenuation, gen. 48)
E	VLE	ELE	east horizontal " (36-48 db attenuation, gen. 42)
N	VLN	ELN	north horizontal " "
E	VHE	EHE ¹	east horiz high gain velocity (0-30 db attenuation, seldom used)
N	VHN	EHN ¹	north horiz high gain velocity (0-30 db atten, seldom used)
V	EHZ	EHZ ¹	high gain, digital station (CREST, ANSS)
F	VFZ	EHZ-10 ¹	very low gain velocity vertical (54-80 db atten., gen. 72)
G	VFN	ELN ¹	" north "
H	VFE	ELE ¹	" east "
U	VDZ	EHZ ^{1,2}	hi gain seis., digital (DST), vertical
W	VDN	EHN ^{2,3}	hi gain seis., digital (DST), north
X	VDE	EHE ^{2,3}	hi gain seis., digital (DST), east
U	EHZ	EHZ	hi gain seismometer, digital (Nanometrics, K2), vertical
W	EHN	EHN	hi gain seismometer, digital (Nanometrics, K2), north
X	EHE	EHE	hi gain seismometer, digital (Nanometrics, K2), east
W	VDN	EP2 ^{2,3}	hi gain seismometer in borehole with unknown orientation
X	VDE	EP3 ^{2,3}	hi gain seismometer in borehole with unknown orientation
W	EP2	EP2	hi gain seismometer in borehole with unknown orientation
X	EP3	EP3	hi gain seismometer in borehole with unknown orientation
D	VL1	EL1	additional rotated velocity horizontal (rare)
O	VL2	EL2	"

Accelerometers

I	ADZ	HNZ ^{1,2,3}	vert force-balance-accel., digital DST (2.0g vv low gain)
J	ADN	HNN ^{1,2,3}	north " "
K	ADE	HNE ^{1,2,3}	east " "
I	ADZ	HN1 ^{2,3}	vert borehole FBA, digital
J	ADN	HN2 ^{2,3}	borehole FBA, digital, unknown orientation
K	ADE	HN3 ^{2,3}	borehole FBA, digital, unknown orientation
I	HN1	HN1	vert borehole FBA, digital

J	HN2	HN2	borehole FBA, digital, unknown orientation		
K	HN3	HN3	borehole FBA, digital, unknown orientation		
I	ASZ	HNZ ¹	vert force-balance-accel. (2.0g v. v. low gain), analog		
J	ASN	HNN ¹	north	"	"
K	ASE	HNE ¹	east	"	"
A	AFZ	HLZ	vert	"	(0.2g very low gain)
B	AFN	HLN	north	"	"
C	AFE	HLE	east	"	"
I	HLZ	HNZ ²	vert Episensor accel., digital system, old L code		
J	HLN	HNN ²	north	"	"
K	HLE	HNE ²	east	"	"
I	HNZ	HNZ	vert Episensor accel., digital system, correct N code		
J	HNN	HNN	north	"	"
K	HNE	HNE	east	"	"
I	BLZ	BNZ	vert Episensor accelerometer, 50 sps, old L code		
J	BLN	BNN	north	"	"
K	BLE	BNE	east	"	"
I	BNZ	BNZ	vert Episensor accelerometer, 50 sps, correct N code		
J	BNN	BNN	north	"	"
K	BNE	BNE	east	"	"

Broadband velocity stations (generally also have accelerometers)

1	HHZ	HHZ	vert broad band (Guralp, Nanomet., Reftek, Kinematics, 100 sps)		
2	HHN	HHN	north	"	"
3	HHE	HHE	east	"	"
4	BHZ	BHZ	vert broad band (Guralp, 50 samples/sec)		
5	BHN	BHN	north	"	"
6	BHE	BHE	east	"	"

Other USGS channels

P	DDI	HV1 ²	dilatometer, digital telemetry (gain 1), isotropic orientation
P	HV1	HV1	dilatometer, digital telemetry (gain 1)
P	DSI	HV1-40 ¹	dilatometer (gain 1)
Q	DFI	HV1-20 ¹	" (gain 12)
R	DLI	HV1 ¹	" (gain 50)
S	DHI	HV1-10 ¹	" (gain 200)
T	T	AT	time code (CUSP recording)

UC Berkeley WA stations, USGS compatible amplitudes from the calnet catalog:

L	WLN	EHN ¹	NS Wood-Anderson torsion (2100X - 2800X)
M	WLE	EHE ¹	EW Wood-Anderson "
X	WFN	ELN ¹	NS lo-gain torsion (BKY 700X, CIT 100X)
Y	WFE	ELE ¹	EW lo-gain torsion (BKY 700X, CIT 100X)

Older UC Berkeley stations, UCB data:

L	EHN	EHN ¹	NS Wood-Anderson torsion (2100X - 2800X)
M	EHE	EHE ¹	EW Wood-Anderson "

V	SHZ	SHZ	Vert Willmore MK II, Benioff or other
X	ELN	ELN ¹	NS lo-gain torsion (BKY 700X, CIT 100X)
Y	ELE	ELE ¹	EW lo-gain torsion (BKY 700X, CIT 100X)

**The following codes are for the Caltech Terrascope or Berkeley BDSN stations:
This constitutes a standard set present at every UCB BDSN station.**

1	HHZ	HHZ	vert very broad band (analog telem., CUSP recording, 100 sps)
2	HHN	HHN ³	north " "
3	HHE	HHE ³	east " "
4	BHZ	BHZ	vert very broad band (Streckeisen STS-2/VBB, 20 samples/sec)

5	BHN	BHN	north	"	"
6	BHE	BHE	east	"	"
7	LHZ	LHZ	vert	long period (Streckeisen STS-2/UVBB, 1 sample/sec)	
8	LHN	LHN	north	"	"
9	LHE	LHE	east	"	"

I	HLZ	HNZ	vert	FBA-23	accelerometer, 80 or 100 sps, old L code
J	HLN	HNN ³	north	"	"
K	HLE	HNE ³	east	"	"
I	HNZ	HNZ	vert	FBA-23	accelerometer, 80 or 100 sps, correct N code
J	HNN	HNN	north	"	"
K	HNE	HNE	east	"	"

BERKELEY SEED USAGE:

(-) indicates seldom used codes

The following channels use SEED codes, USGS Menlo Park uses only SEED codes:

Wood-Anderson response stations:

--- EHN,³ EHE: Wood-Anderson analog (2800X, 0.8 s) (pre 1994)
 --- ELN,³ ELE: Low-gain Torsion (100X or 700 max, paper records)
 --- BHN, BHE: Wood-Anderson synthetic (0.8 s); High-gain Torsion (14 000 max)
 --- HHN,³ HHE: Wood-Anderson synthetic (0.8 s); High-gain Torsion (14 000 max)
 --- HLN,³ HLE: Wood-Anderson synthetic (0.8 s); High-gain Torsion (14 000 max)

Broad band BDSN stations:

HHZ, HHN, HHE: 80 or 100 sps Streckeisen STS-2/VBB, STS-1/UVBB, Guralp CMG-40T,
 or Teledyne Geotech 8700, SL-210 or SL-220
 BHZ, BHN, BHE: 20 sps Streckeisen STS-2/VBB, STS-1/UVBB, or Guralp CMG-40T
 LHZ, LHN, LHE: 1 sps Streckeisen STS-1/UVBB or STS-2/VBB,
 Teledyne Geotech SL-210 or SL-200, Guralp CMG-3 or
 Streckeisen STS-1/UVBB (CMB)

Force balance accelerometers:

HLZ, HLN, HLE: 80 or 100 sps Kinemetrics FBA-23
 CL1, CL2, CL3: Wilcoxin borehole accelerometer, 500 sps, rotated horizontals
 HL1, HL2, HL3: Wilcoxin borehole accelerometer, 100 sps, rotated horizontals
 BL1, BL2, BL3: Wilcoxin borehole accelerometer, 20 sps, rotated horizontals
 BLZ, BLN, BLE: 20 or 50 sps Kinemetrics FBA-23 (-)
 LLZ 1 sps Kinemetrics FBA-23 (-)
 HNZ, HNN, HNE: 80 or 100 sps Kinemetrics FBA-23
 CN1, CN2, CN3: Wilcoxin borehole accelerometer, 500 sps, rotated horizontals
 HN1, HN2, HN3: Wilcoxin borehole accelerometer, 100 sps, rotated horizontals
 BN1, BN2, BN3: Wilcoxin borehole accelerometer, 20 sps, rotated horizontals
 BNZ, BNN, BNE: 20 or 50 sps Kinemetrics FBA-23 (-)
 LNZ 1 sps Kinemetrics FBA-23 (-)

Codes used occasionally, for example at the BKS vault or special stations:

BHR, BHT: 20 sps Streckeisen STS-1/UVBB
 LHR, LHT: 1 sps Streckeisen STS-1/UVBB (360 sec) or STS-1/VBB (300 sec)
 VHZ, VHN, VHE: 0.1 sps very long period channel
 UHZ, UHN, UHE: 0.01 sps ultra long period channel
 MHZ, MHN, MHE: DWSSN station at CMB, Guralp CMG-3

Older codes used at the BKS vault:

1=vertical, 2,3=sometimes 45 degree rotated, sometimes normal
 horizontals
 EH2, EH3: Wood-Anderson synthetic (0.8 s); High-gain Torsion (14 000 max)
 BH1, BH2, BH3: 20 sps Sprengnether S-5100 ULPV Broadband
 HH1, HH2, HH3: 100 sps Sprengnether S-5100 ULPV Filtered Displacement
 LH1, LH2, LH3: 1 sps Sprengnether S-5100 ULPV Broadband
 UH1, UH2, UH3: 0.01 sps Sprengnether S-5100 ULPV ultra long period, analog

LHZ : Press-Ewing (15.0 s) (at BRK before 1995)

Other digital stations:

DP1 DP2, DP3: Borehole geophone, 500 sps
EP1, EP2, EP3: Borehole geophone, 100 sps (-)

Older analog stations:

SHZ or SH1,2,3: 50 sps Willmore MK II, Benioff 100 kg (0.8 s) or 14.7 kg,
Geotech S-13 or GS-13, Filtered Geotech 7507 or
Mark Products L-4C

CALTECH SEED USAGE FOR TERRASCOPE STATIONS:

HHZ, HHN, HHE: 100 sps, Streckeisen, analog telemetry, CUSP recording
BHZ, BHN, BHE: 20 sps Streckeisen STS-2/VBB, digital telemetry
HLZ, HLN, HLE: 100 sps low gain
ELZ, ELN, ELE: 100 sps Kinematics FBA-23
EHZ, EHN, EHE:
LHZ, LHN, LHE:
BLZ, BLN, BLE:

UNIVERSITY OF NEVADA RENO SEED USAGE:

SHN, SHE: Teledyne Geotech SL-210 & SL-220
HHZ, HHN, HHE: 100 sps Teledyne Geotech SL-210 & SL-220

Notes:

¹ No uniqueness backward. Both the VHZ code for analog, low dynamic range stations and VDZ code for high dynamic range (DST or Nanometrics) digital stations map into the same EHZ SEED code. This means that once the mapping to SEED codes takes place, that any differences must be handled on a station-by-station basis. For example, coda durations from VDZ stations before 8/18/2000 are corrupted, and it will no longer be possible to use the component code to mark these as unusable. Similarly, both the analog ASZ accelerometers and the digital ADZ accelerometers become the SEED code HNZ.

Some stations, like older UCB Wood-Anderson stations, are referred to by the USGS code WLN if the source was the NCSN catalog, and EHN if the source was UCB. Data can be present for either version of the station or both.

² Rename. In September 2000 the existing Nanometrics and Kinematics-2 digital stations were “renamed” by using new component codes to label them as they were recorded. The rename did not occur by overwriting older, archived data, but that was expected to happen sometime in the future. Both old and new codes are required to completely support these stations. This rename was to bring the codes into SEED compliance, and sometimes to distinguish them from analog stations in the processing.

³ No uniqueness forward. Note that the mapping from NCSN to SEED code is not unique, and that the same NCSN code can be used for stations of different types that have different SEED codes.

Table 4. STATION OR PHASE REMARK CODES

(These codes are not universally applied to all phases; _ stands for a blank space).

1-let-code	Meaning	Original 3-letter codes						
A	Calibration card	CAL						
B	Coda read to backgrd.	BGC	BGK	BCK				
C	Clipped	CLP	CMX					
D	Dead trace	DED	OUT	NNE	DWK	_NE	NE_	N/E
E	Emergent	VVE						
F	F-P uncertain	FPQ	FP?					
G	Guessed time	GES	GUS	EST				
M	Max amplitude read	MAX	MX_					
N	Noisy trace	NOI	NSE	NOY	NOE			
P	Amplitude is of P wave	PMX						
S	Spiky trace	SPI	SPK					

T	Cross-talk	CF	CF	CF?	CFQ
W	Weak signal	WEK	WKE	VWK	

Table 5. 1-LETTER REGION CODE

(First letter of N.Calif. USGS stations. Regions in parentheses are not used in the normal USGS code convention, but were devised for Southern California).

A	Auburn region	N	Napa Valley region
B	San Juan Bautista region	O	Oroville region
C	Calaveras region	P	Parkfield region
D	Mojave desert	Q	(Southern Nevada)
E	(Elsinore fault region)	R	(Riverside region)
F	(San Fernando and Los Angeles basins)	S	Santa Barbara region
G	Geysers region	T	(Tejon pass region)
H	Hollister region	U	(Northern Nevada (UNR net))
I	(Imperial valley)	V	Oregon
J	San Jose region	W	Walker pass region
K	Klamath mountain region	X	(Mexico)
L	Lassen and Shasta region	Y	
M	Melones and Mammoth regions	Z	

Table 6. 2-LETTER PORTABLE NET CODES

The 4-letter station code for portables generally consists of the 2-letter net code, a 1-digit number or letter (number of the station within the portable deployment), and the letter 'P' for portable. The catalog does not have data from a few of the portable deployments listed below. USGS Menlo portable deployments starting in 1998 may use an IRIS-assigned XL as the net code and may not follow any standard portable site-code naming.

	Region or name	Dates	Operator
BA, BB, BC, BD, BE, BF, BL & BM			
	Bear Valley	7/74-1/75	USGS 10-day
BI	Bishop	1978	
CA	Long Valley Caldera	3/84	USGS
CH	Chalfant Valley	7/86	USGS
CL	Long Valley	6-9/81	CDMG
CO	Coalinga	5-9/83	USGS
CP	Coalinga GEOS	5/83	USGS digital GEOS
CS	Coso Hot Springs	5-6/77	USGS Centipede
DA, DB, DD, DE, DF, DG, DH, DI, DJ, DK, DL, DM, DS:			
	Dry Lake centipede (BV)	9-11/78	USGS
DC	Dos Cuadras Ocean Bot.	12/75-1/76	USGS OBS
DU	Durwood Meadows	10-11/83	USGS 5-day
EU	Eureka & Cape Mendocino	11-12/80	USGS
GE	Geysers	8-12/81	USGS
HP	Bear Valley	7-9/67	USGS
JA	Long Valley	1/83	USGS
KE	Kettleman Hills	8/85	USGS
LA	Lassen Park	7-10/80	USGS 5-day
LI	Livermore	1-2/80	LLL
MC	Mono Craters	7-8/82	USGS
MD	Mount Diablo	6-7/70	USGS
MH	Morgan Hill GEOS	4-5/84	USGS digital GEOS
MI	Morgan Hill 5-day	4-5/84	USGS
ML	Mammoth Lakes	5-6/80	USGS
MM	" "	"	Caltech
MN	" "	"	UNR
MO	" "	"	USGS digital GEOS
MP	" "	78-82	CDMG
MQ	Mammoth Mountain	6/23-27/89	USGS - GEOS
MR	Mammoth	8/82	USGS

NB	North Bay area	12/03-12/04	USGS, Jack Boatwright
OR	Oroville	8/75-76	DWR
OW	"	8/75	Woodward Clyde
PB	Point Buchon	12/80-5/81	USGS
PK	Parkfield		
PM	Point Mugu	2-4/73	USGS
RO	Rocklin	6/78	CDMG
RV	Round Valley	11/84	USGS
SA	San Andreas	1-5/70	USGS
SB	San Juan Bautista	5-6/81	USGS
SC	Santa Cruz Mtns.	9/67	USGS
SH	Shasta	8/78	USGS
SP	Shasta (Stevens Pass)	8/78	USGS
SR	Santa Rosa	10/69	USGS
ST	Shasta (tennant)	1/81	USGS
SU	Point Sur	1-2/84	USGS
UA	UNR Mammoth	10/78	UNR
UB	UNR Mammoth	10-11/79	UNR
UD	UNR Round Valley	11/84	UNR
UE	UNR Chalfant Valley	7/86	UNR
UF	UNR Mammoth	5/82	UNR
UO	Union Oil, Medicine Lake	8/84	Union Oil

(XL) Santa Clara Valley Experiment, 6-11/1998, USGS

Table 7. REGIONS BY 3-LETTER CODE

(Regions labeled with '%' are aggregates of smaller regions and should not appear on the summary cards.)

Code	Name	region number
ALM	Lake Almanor	58
ALU	Alum Rock	21
ANN	Anno Nuevo	34
AUB	Auburn	60
BAK	Bakersfield	75
BAR	Bartlett Springs Fault	49
BIT	Bitterwater Valley	12
BLM	Black Mountain	2
BRC	Basin & Range Calif %	64
BUS	Busch Fault	5
BVL	Bear Valley	11
CAS	Casa Diablo Mtn. (VOT)	95
CHA	Chalk Bluffs (VOT)	97
CHV	Chalfant Valley (BRC)	79
COA	Coalinga	31
CON	Concord Fault	18
COS	Coso Range (BRC)	81
CRV	Ciervo Hills	30
CYN	Coyote North	23
CYS	Coyote South	24
DAN	Danville	19
DEL	Del Norte	52
DEV	Death Valley (BRC)	85
DOM	Resurgent Dome (LVC)	91
EMO	East Moat (LVC)	89
EUR	Eureka	51
GAR	Garlock Fault	83
GEY	Geysers	43
GLA	Glass Mtn. (MOB)	77
GOL	Gold Hill	15
GRN	Greenville Fault	26

GVL	Green Valley Fault	46
HAM	Mt. Hamilton	27
HAY	Hayward Fault	16
HCF	Hilton Crk. Flt. (LVC)	93
HOL	Hollister	9
INC	Inyo Craters (LVC)	86
IWV	Indian Wells Val. (BRC)	82
JQN	San Joaquin Valley	54
KAI	Kaiser Peak	65
KLA	Klamath Mountains	55
KON	Konocti Bay	44
LAS	Lassen	57
LOM	Loma Prieta	3
LVC	Long Valley Caldera %	66
MAA	Maacama Fault	48
MAM	Mammoth Mtn. (LVC)	92
MAR	Marin	41
MCA	Mono Caldera (MOB)	74
MEN	Mendocino Escarpment	50
MID	Middle Mountain	14
MIS	Mission Fault	17
MOB	Mono Basin %	63
MOD	Modoc Plateau	72
MOL	Mono Lake (MOB)	78
MON	Monterey Bay	35
MOR	Mt. Morrison (RSM)	98
NAP	West Napa Fault	45
NEV	Nevada	73
NMO	North Moat (LVC)	88
ORE	Oregon	71
ORO	Oroville	59
ORT	Ortigaleta Fault	28
OWV	Owens Valley (BRC)	84
PAI	Paicines	10
PAN	Panoche Pass	29
PAR	Point Arena	47
PIN	Pinnacles	8
PON	Pacific Ocean N	70
POS	Pacific Ocean S	103
QUI	Quiensabe	25
ROB	Paso Robles	38
ROG	Rogers Creek Fault	42
RSM	Red Slate Mountain %	68
RVL	Round Valley (VOT)	96
SAC	Sacramento Valley	53
SAL	Salinas Valley	36
SAR	Sargent Fault	4
SBA	Santa Barbara	94
SCA	Southern Calif.	69
SCV	Santa Clara Valley	33
SFB	South S.F. Bay	32
SFL	San Felipe	22
SFP	S.F. Peninsula	1
SHA	Shasta	56
SHE	Sherwin Lakes (RSM)	99
SIL	Silver Peak (RSM)	100
SIM	Simmler	40
SJB	San Juan Bautista	6
SLA	Slack Canyon	13
SMO	South Moat (LVC)	90
SSM	San Simeon	39
STN	Stone Canyon	7

SUN	Sunol	20
SUR	Big Sur (Hosgri Fault)	37
VOT	Volcanic Tableland %	67
WAK	Walker Lane	62
WCN	Wheeler Crest No. (RSM)	101
WCS	Wheeler Crest So. (RSM)	102
WHI	White Mountains (BRC)	80
WMO	West Moat (LVC)	87
WWF	White Wolf Falut	76
YOS	Yosemite	61

Table 8. MULTIPLE VELOCITY MODELS

Different crustal models and station delay sets are used for regions in Northern California. Events falling between regions will use a combination of 2 or 3 models. Two regions have different models for either side of the San Andreas Fault. An event in a dual-model region uses separate models for stations on different sides of the fault regardless of which side of the fault the epicenter is on. The Loma Prieta region uses model LOM for stations on the west (Pacific) side and model LON for stations on the east (North American) side. The code LOM labels all events that use these two models. The Bear Valley region uses model GAB for stations on the Gabilan (west) side and model DIA for stations on the Diablo (east) side. The three Parkfield areas use identical models but slightly different sets of station delays.

Similarly, some adjacent models are paired in the sense that the models are identical. The station delays, however, differ slightly. These include the San Francisco peninsula north (PEN) and south (PES), and 3 Parkfield models (PGH, PMM, and PSM).

The velocity models used by Hypoinverse for locating the NCSN catalog have linear velocity gradients within layers and no first-order velocity discontinuities. Most models were originally homogeneous layer models, and were often "smoothed" by replacing many velocity steps with fewer layers with gradients. This gradient approach eliminates the artificial discontinuities of layer models, improves convergence and stability, and eliminates multiple refractions at the same take off angle.

A description of the models and maps of the regions assigned to each model are published in *The Northern California Seismic Network Bulletin 1992* by Oppenheimer et al., USGS open file report 93-578. The report also includes a set of station delays for each model, but these have been slightly improved by an additional iteration of removing the average station residual from a set of earthquakes from the catalog. Stations that have moved a short distance (< 1 km) have duplicate delays unless there is enough data for an independent delay determination. Following the next table is a list of the velocity-depth points of the gradient models: the actual model connects these points with gradients, and the last velocity is the constant half-space velocity underlying the model. I also list the original homogeneous layer models specified by the depth to layer top and the constant layer velocity.

<u>Code</u>	<u>Name</u>	<u>Delay</u>	<u>Source of original model</u>	<u>How</u>
		<u>status</u>		<u>derived</u>
AUB	Auburn	2	Eaton & Simirenko (OFR 80-604, 1980)	test&modify
BAE	Bartlett Spr east	2	Castillo pers. comm. (1991)	VELEST
BAR	Bartlett Spr Fault	2	Castillo pers. comm. (1991)	VELEST
BAS	Basin & Range	2	averaged Prodehl (Prof Pap 1034, 1979)	refract
COA	Coalinga	2	Eaton OFR 85-44 (1985)	test&modify
CON	Concord-Calaveras	2	Klein pers. comm. (1991)	VELEST
COY	Coyote Lake	2	Reasenber & Ellsworth (JGR 1982)	VELEST
CST	Central Coast	2	Poley & Eaton pers. comm.	test&modify
DIA	Diablo-Bear Valley	2	Dietz pers. comm. &	VELEST
	(west)		Walter & Mooney (BSSA 1982)	refract
EBY	East Bay (unused)	2	Olson pers. comm. &	
			Ellsworth & Marks OFR (1980)	VELEST
GAB	Gabilan-Bear Valley	2	Dietz pers. comm. &	VELEST
	(east)		Walter & Mooney (BSSA 1982)	refract
GEY	Geysers	2	Eberhart-Phillips & Oppenheimer JGR '84	VELEST
HAY	Hayward Fault	2	Klein pers. comm. (1990)	VELEST
LAS	Lassen	2	S. Walter pers. comm.	VELEST
LEW	Mt. Lewis	2	Klein pers. comm. (1990)	VELEST
LIV	Livermore-Antioch	2	Klein pers. comm. (1991)	VELEST
LOM	Loma Prieta (west)	2	J. Olsen and M. Zoback (1995)	VELEST

LON	Loma Prieta (east)	2	J. Olsen and M. Zoback (1995)	VELEST
MAA	Maacama Fault	2	Castillo pers. comm. (1991)	VELEST
MAM	Mammoth Lakes	2	Kissling (PhD thesis 1986?) & Cockerham & Kissling pers. comm.	refract & inversion
MAN	Maacama North	2	Castillo pers. comm. (1991)	VELEST
MEN	Mendocino	2	Magee pers. comm. (1991)	VELEST
MOR	Morgan Hill	2	Cockerham & Eaton (USGS Bulletin 1639, 1987)	VELEST
NBY	North S.F. Bay	2	Eberhart-Phillips & Oppenheimer (JGR 1984)	VELEST
NCG	N. Calif. gradient	2	default model derived from:	
NCA	N.Cal layer (unused)	2	standard NCSN, Eaton pers. comm.	test&modify
PAR	Parkfield (unused)	2	Poley & Eaton pers. comm.	test&modify
PEN	SF Peninsula north	2	Olson (Proc. Rec. Crus. Mvmts. 1987?)	VELEST
PES	SF Peninsula south	2	Olson (Proc. Rec. Crus. Mvmts. 1987?)	VELEST
PGH	Park.-Gold Hill	2	Poley & Eaton pers. comm.	test&modify
PMM	Park.-Middle Mtn.	2	same as PGH.	test&modify
PSM	Park.-Simmler	2	same as PGH	test&modify
PTA	Pt Arena, Ft Bragg	2	Castillo pers. comm. (1991)	VELEST
SCA	Southern Calif.	2	Jones pers. comm.	refract?
SHA	Shasta & Oregon	2	average from Zucca et al. (JGR 1986)	refract
SJB	San Juan Bautista	2	Moths pers. comm.	VELEST
	(SJB replaced by extended Loma Prieta model)			
TRA	Transverse Ranges	2	Prodehl PP-1034 (1979)	refract
TRE	Tres Pinos	2	Dietz pers. comm. & Walter & Mooney (BSSA 1982)	VELEST
			Jones & Dollar (BSSA 1986)	refract
WAL	Walker Pass	2		test&modify

The status codes for the station delays are:

- 1 Delays are from original investigator for layer model.
- 2 Delays refined for present region and gradient model from original delays.

Depth-Velocity points for models with linear gradients in layers

Earthquake locations are processed by Hypoinverse-2000 using linear gradient crustal models.
Code, Depth Z (km), Velocity V (km/s)

AUB	Z 0.00 1.00 34.00 36.00
	V 4.80 6.20 6.85 8.00
BAE	Z 0.00 4.50 18.60 28.50
	V 4.20 5.80 6.05 7.80
BAR	Z 0.00 2.00 19.00 21.00 29.00 31.00
	V 4.00 5.46 6.08 6.60 6.80 7.80
BAS	Z 0.00 7.10 28.60 32.60
	V 4.00 5.95 6.60 7.85
COA	Z 0.00 2.20 14.00 26.00 30.00
	V 2.00 4.30 6.25 6.80 7.95
CON	Z 0.00 2.00 12.00 24.00 26.00
	V 2.50 4.70 5.77 6.12 7.95
COY	Z 0.00 1.40 5.80 10.60 24.00 26.00
	V 3.80 5.30 6.12 6.37 6.59 8.00
CST	Z 0.00 2.50 8.00 23.80 26.80
	V 2.95 5.13 6.20 6.65 8.12
DIA	Z 0.00 1.50 5.80 14.40 15.60 29.00 31.00
	V 2.45 4.62 5.80 6.05 6.85 7.15 7.95
GAB	Z 0.00 4.00 22.50 25.50
	V 3.73 6.07 6.47 7.95
GEY	Z 0.00 3.00 8.00 20.00 22.00
	V 4.10 5.47 5.75 6.02 7.90
HAY	Z 0.00 3.00 9.00 24.00 26.00

CON 2.96 0.0, 3.19 1.0, 4.72 2.0, 4.95 4.0, 5.51 7.0, 5.96 12.0, 7.95 25.0
 COY 4.84 0.0, 5.39 1.5, 5.70 3.0, 5.89 4.25, 6.13 5.5, 6.20 6.75,
 6.28 8.0, 6.41 10.0, 6.50 12.5, 8.00 25.0
 CST 3.0 0.0, 5.7 1.5, 6.23 8.0, 6.43 12.33, 8.12 25.33
 DIA 3.50 0.00, 5.01 1.50, 5.88 5.10, 6.91 15.00, 7.95 29.00
 EBY 3.4 0.0, 4.7 1.0, 5.20 3.0, 5.6 5.0, 5.7 7.0, 5.8 9.0, 6.0 11.0,
 6.8 13.0, 8.0 25.0
 GAB 3.70 0.00, 5.45 1.30, 6.13 4.50, 6.36 10.00, 7.95 24.00
 GEY 4.43 0.0, 5.12 1.50, 5.47 3.00, 5.58 4.25, 5.62 6.0, 5.86 8.0, 7.9 21.0
 HAY 3.77 0.0, 4.64 1.0, 5.34 3.0, 5.75 6.0, 6.00 9.0, 6.22 14.0,
 7.98 25.0
 LAS 4.3 0.0, 5.5 2.0, 6.0 4.5, 6.17 6.0, 6.35 9.0, 8.05 30.0
 LEW 3.60 0.00, 5.03 1.00, 5.24 2.00, 5.66 4.00, 5.88 8.00, 5.91 10.00,
 6.16 14.00, 7.95 25.00
 LIV 2.56 0.0, 2.75 1.0, 3.56 2.0, 4.74 4.0, 5.60 7.0, 6.28 12.0,
 7.95 25.0
 LOM 3.36 0.00, 4.58 1.00, 5.25 2.00, 5.91 5.00, 6.13 8.00, 6.22 13.00,
 6.53 18.00, 8.00 25.00
 LON 3.00 0.00, 3.99 1.00, 5.57 2.00, 6.01 5.00, 6.32 8.00, 6.46 13.00,
 6.58 18.00, 7.98 25.00
 MAA 4.15 0.00, 4.65 1.00, 5.49 2.50, 5.57 4.00, 5.63 6.50, 5.72 8.00,
 5.81 10.00, 5.86 12.00, 5.91 14.00, 6.08 16.00, 6.68 20.00, 7.76 25.00,
 7.80 30.00
 MAM 3.55 0.0, 3.57 0.5, 3.70 1.0, 5.35 2.0, 5.67 3.0, 5.90 5.0,
 6.02 7.0, 6.07 10.0, 6.10 14.0, 6.18 18.0, 6.67 30.0, 8.00 50.0
 MAN 4.36 0.00, 5.46 1.50, 5.60 3.50, 5.63 5.00, 5.66 7.50, 5.78 10.00,
 6.00 12.50, 6.21 15.00, 6.68 20.00, 7.76 25.00, 7.80 30.00
 MEN 3.90 0.00, 5.10 3.00, 5.51 6.00, 5.95 12.00, 6.78 18.00, 7.60 24.00,
 7.83 27.00, 7.903 0.00
 MOR 3.67 0.00, 4.80 0.50, 5.27 2.00, 5.76 4.20, 6.05 10.00, 6.20 14.00,
 7.60 25.00
 NBY 4.43 0.0, 5.12 1.5, 5.47 3.0, 5.58 4.25, 5.62 6.0, 5.86 8.0, 7.9 21.0
 NCA 4.00 0.00, 5.90 3.50, 6.80 15.00, 8.05 25.00
 PAR 1.42 0.00, 3.24 0.25, 4.82 1.50, 5.36 2.50, 5.60 3.50, 5.87 6.00,
 6.15 9.00, 6.60 15.00, 8.00 25.00
 PEN 2.94 0.00, 4.21 1.00, 5.20 2.00, 5.93 5.00, 6.16 8.00, 6.25 11.00,
 6.30 14.00, 6.35 17.00, 8.06 23.50
 PGH same as PAR
 PMM same as PAR
 PSM same as PAR
 PTA 4.40 0.00, 5.30 1.50, 5.56 3.50, 5.66 5.00, 5.67 7.50, 5.68 10.00,
 5.85 12.50, 6.08 15.00, 6.68 20.00, 7.76 25.00, 7.80 30.00
 SCA 5.5 0.0, 6.3 5.5, 6.7 16., 7.8 32.
 SHA same as LAS
 SJB 3.483 0.0, 4.426 0.5, 5.101 1.0, 5.676 3.0, 5.897 5.0, 6.140 7.0
 6.212 9.0, 6.284 11.0, 6.412 13.0, 6.435 15.0, 6.812 18.0, 8.0 25.0
 TRA same as SCA
 TRE 3.57 0.00, 5.35 1.50, 5.83 5.10, 6.86 15.00, 7.95 29.00
 WAL 3.5 0.0, 5.8 1.0, 6.2 8.0, 6.9 22.0, 7.9 36.0

Table 9. WEIGHT CODES FOR TIMES, AMPLITUDES & DURATIONS

P & S time weights. The weight code is assigned by the analyst and is translated into an applied numerical weight used in the location. The actual weight used in hypoinverse is this applied weight, multiplied by the distance weight times the residual weight. The latter two weights start at 1.0 and decrease to 0.0 for very distant and very high residual stations. The resulting weight is normalized (and can thus exceed 1.0), used in the inversion, and then output as the "weight used". The "weight used" shows the relative influence of different picks on the solution.

The subjective error is the one the analyst envisions when assigning the weight code. The formal numerical error is the standard timing error (a constant for all earthquakes) divided by the applied weight. The formal error only influences

the location errors like *erh* and *erz*. The standard timing error is subjectively set and is presently 0.10 sec. It is used to scale the covariance matrix and is the net result of all unmodeled timing errors such as reading error and the deviation of the real earth from the assumed crustal model.

<u>code</u>	<u>applied</u> <u>weight</u>	<u>subjective</u> <u>error, sec</u>	<u>formal</u> <u>error sec</u>
0	1.0	0.02	0.10
1	0.5	0.10	0.20
2	0.2	0.20	0.50
3	0.1	0.30	1.00
4-9	0.0	-	-

Amplitude and duration magnitude weight codes. The applied weights are used in the calculation of the weighted median event magnitude. Each station magnitude is computed individually and then sorted into increasing order. The weighted median magnitude is the magnitude corresponding to the point in the sorted list which has accumulated half of the total weight of all readings.

<u>code</u>	<u>applied</u> <u>weight</u>
0	1.00
1	0.75
2	0.50
3	0.25
4-9	0.00